

product specifications



SXSUB *Sub-Bass Reinforcement*

- HIGH SOUND PRESSURE LEVELS
- FOR USE IN 3- & 4-WAY SYSTEMS
- FREQUENCY RESPONSE OF 40 - 200Hz
- COMPACT AND VERSATILE DESIGN

Designed as a companion to our SX Series line of full-range speaker enclosures, the SXsub has proven itself to be worthy of any extended low frequency response duty. Capable of extremely high SPL, this enclosure is the perfect match when used in conjunction with other Adamson enclosures - extending low-end frequency response to below 40Hz. The SXsub is equipped with two AW18 Kevlar bass drivers mounted in a tuned, vented and heavily braced cabinet. Supplied with integral castors for easy tilt and roll, this cabinet is lightweight, compact and powerful.



technical specifications



SXSUB Sub-Bass Reinforcement

DESCRIPTION

Compact, easily transported, sub-bass loudspeaker designed to provide high SPL extended bass to all Adamson full-range enclosures. The SXsub is equipped with two AW18 Kevlar bass drivers in a tuned, vented enclosure. Integral 'Tilt & Roll' castors are supplied as standard equipment.

APPLICATIONS

- Live Concert Reproduction
- Drum Fill & Side Fill Monitoring
- Theaters
- Houses of Worship
- Dance Clubs

FEATURES

- Twin 18" Kevlar Bass Drivers
- Frequency Response of 40 - 200Hz
- Compact
- Durable, Dual Component Finish
- Computer Punched Steel Grille
- Roadworthy Construction

PHYSICAL DATA

Dimensions & Weight	
Height (cm)	42" (106.7)
Width (cm)	24.6" (62.5)
Depth (cm)	24.5" (62.2)
Weight (kg)	135 lbs. (61.4)
Box Finish	Waterborne Acrylic
Hardware Finish	Black Bake Enamel
Accessories	2 x Heavy Duty Urethane Wheels
Cabinet Construction	Rugged 5/8" (15mm) Baltic Birch

TECHNICAL DATA

Frequency Response ($\pm 3\text{dB}$)	40 Hz - 200 Hz
Frequency Range	
Xover Preset	35 Hz - 80 Hz
Maximum SPL (Continuous)	
Xover Preset	128.7dB
System Type	Dual 18" front loaded
	LF 2 x AW18 18" Kevlar Low Frequency Driver (2 x 8 Ohms)
Power Handling (AES / Program / Peak) x 2	
	600 / 1200 / 2400
Sensitivity (2.83V @ 1m)	103.7dB
Connectors	Neutrik Speakon™ NL4



Adamson Systems Engineering Inc.
1401 Scugog Line 6, Port Perry, ON L9L 1B2
T: [905] 982 0520 F: [905] 982 0609
www.adamsonproaudio.com
sales@adamsonproaudio.com

Specifications Are Subject To Change Without Notice

